



Led strip : 75 led par meter SMD5730

5730-75-DW-20-24V

VOLTRON® LED strip for the professional with unique patented waterproof design (no more visible difference in color between IP20 and IP54/68). LED strip is equipped with 3 ounce PCB for extremely durable retention of light efficiency and cooling. MacAdam 3 LED chips guarantee always a consistent color level (BIN and BATCH codes). Packed per roll of 5 meters, provided with 30cm AWG cable on both sides. VOLTRON® 24V dimmable LED strip is mainly used for direct or indirect mood lighting - High Power Lumen - Epistar LED die - SMD5730 InGaN Blue Chip - 75LEDs/m - 2700K - IP20 - 24,75W/m - 2050Lm - Advice = max. up to 10M/power supply (constant voltage) - L80 >40.000h - 3 years warranty - In combination with our single ALU-profiles



CCT
4000K

WATT
24,75W/M

IP
20

Lumen
2050Lm

CRI Ra
>80

UGR
<19

MacAdam
4

LED
75/M

VOLT
24V

5M

V

120°

80MM

GARANTIE
3

Technical data


Productnumber	Barcode	CCT	IP value	Led chip
5730-75-DW-20-	LH-650	4000K	20	SMD5730
Number of LED	Wattage	Length	Voltage	Width
75/M	24,75W/M	5M	24V	10MM
CRI Ra	Lxx @Ta=25°C	UGR	MacAdam	Lumen
>80	L80 >40.000	<19	4	2050Lm
Spread angle	Led distance	Dimmable	Cuttable	Cable length
120°	13,3MM	V	80MM	2X30CM AWG
Constant voltage	Packed per	Full package		
V	1	29		

Specification text*

Compact LED light line for flush and surface mounting. Built from 75 'HIGH POWER dimmable' LEDs / m - Ultra Series Epistar SMD5730 with a light spread of 120 ° and double white, ultra-reflective PCB for increased light reflection and accelerated heat dissipation. At the rear with 3M double-sided tape. Standard vacuum packed on a roll of 5 meter in a box. Can be shortened per 8 cm. Equipped with a 30 cm twin AWG cable on both sides. Width 10 mm, thickness 3.5 mm, LED distance 13.3 mm. Generates 24.75W / m and 2050lm at 24V and a light color 4000K (white). IP20 class. Can be connected to Meanwell power supplies (IP67) with a constant voltage. With a color rendering index of > 85. May 'never' be used without ALU profile!

* Available on the website

Photometric diagram



Areas of application

Shops, showroom / All interior spaces (excluding bathroom and kitchen work surfaces) / Lighting of cabinets, cupboard walls / Display lighting / Indirect lighting for ceilings / Surface mounted above a stretch ceiling / Built into gyproc walls or stone walls using an LED profile / For roof overhangs and bathrooms or other damp rooms always use IP54 / Always process the LED strips in an aluminum profile

Extra information

All information, specification texts, photos, technical drawings, connection diagrams, photometric .LDT files can be found via this clickable direct link: https://www.voltron-lighting.com/product/EN/22/650/Led_strip_:_75_led_par_meter_SMD5730--5730-75-DW-20- or can be requested through your contact person.

Direct link website



Product barcode



The Voltron® name and logo as well as product names are part of the Voltron® Lighting Group and are protected by national and international laws.

The usage rights, reproduction rights as well as the intellectual rights are the exclusive property of the Voltron® Lighting Group.

Voltron® pays a lot of attention to the correctness and completeness of the information. However, it cannot be held responsible for any inaccuracy and / or omission. All images and texts are protected under copyright law and may not be used or multiplied without express permission.