
















The Flat Square



TFS-250-DW-24V

The Flat Square by VOLTRON® is a round dimmable LED-downlighter for installation in false ceilings with ultra thin and light housing (only 26mm high!). ALU housing with lateral cooling fins for optimal cooling and long lifespan of the light output. The fixation in the ceiling is done with high-quality springs with extra protective rubbers. Electric connection is done with DC male/female connectors for very fast installation. The diffuse PC light surface ensures a smooth light distribution. This downlighter is also perfect suitable as a wall or floor lighting. TYPE TFS-250x250-DW : 250x250mm - 28W - 2485Lm - 4000K - IP52 class - MacAdam 3 - white - HEIGHT = 26mm (!) - L80 >54.000h. Connectable to Meanwell power supplies (IP67) with constant voltage (not included). Warranty = 5 years.



 CCT 4000K	 WATT 28W	 IP 52	 Lumen 2485Lm	 CRI Ra >85	 UGR <19	 Lx T: 25°C L80 >54.000
 MacAdam 3	 25CM	 25CM	 IK 03	 X	 DIMMABLE V	 GARANTIE 5

Technical data


Productnumber	Barcode	CCT	IP value	Led chip
TFS-250-DW-24V	LH-1128	4000K	52	SMD2835
Voltage	Wattage	Length	Width	Thickness
24V	28W	25CM	25CM	2,6CM
Punch hole	Finish color	CRI	Lxx @Ta=25°C	UGR
15,5~16,5CM	White	>85	L80 >54.000	<19
MacAdam	IK	Spread angle	Lumen	Dimmable
3	03	120°	2485Lm	V
Driver included	Cable length	Constant voltage	Packed per	
X	31CM+33CM	V	2	

Specification text*

Highly efficient square dimmable LED downlight for installation in false ceilings with an ultra thin and light housing. White aluminum visible outer housing with cooling fin structure for optimum long-term operation. At the rear with removable high-quality ALU plate to promote the firmness and accelerated cooling of the LEDs. Fixation in the ceiling is done with 4 spring clips with plastic covered against incision. Electric connection using DC male / female connectors for very fast assembly. The panel has 140 LEDs type Epistar SMD2835. Light control via opaque opal optic from PC for glare protection and maximum luminaire efficiency. Panel can also serve as wall or floor lighting. Dimensions 250x250mm, thickness 26mm and a weight of barely 676gr. Generates 28W and 2485lm at 24V and a light color 4000K (white). IP52 class. IK 03, MacAdam 3, L80 >54.000, UGR <19. Extremely suitable for office spaces, meeting rooms, showrooms, shops, corridors, toilets and classrooms. Can be connected to Meanwell power supplies (IP67) with a constant voltage. With a color rendering index of > 85. Equipped with photo metric report and IES file for elaboration in DIALux.

* Available on the website

Photometric diagram




Areas of application

Shops and showrooms / Toilets / Corridors / Installation vertically into walls as ground or wall lighting / Integration into false, gyproc or fixed ceilings / Private homes / Shipbuilding

Extra information

All information, specification texts, photos, technical drawings, connection diagrams, photometric .LDT files can be found via this clickable direct link: https://www.voltron-lighting.com/product/EN/56/1128/The_Flat_Square--TFS-250-DW-24V or can be requested through your contact person.

Direct link website



Product barcode



The Voltron® name and logo as well as product names are part of the Voltron® Lighting Group and are protected by national and international laws.

The usage rights, reproduction rights as well as the intellectual rights are the exclusive property of the Voltron® Lighting Group.

Voltron® pays a lot of attention to the correctness and completeness of the information. However, it cannot be held responsible for any inaccuracy and / or omission. All images and texts are protected under copyright law and may not be used or multiplied without express permission.